



Jim Persons
jimpersons@safetypride.com
707-889-0881

Heavy Equipment - “Two Major Hazards”

Heavy equipment such as cranes, bull dozers, front loaders, dump trucks, excavators, etc. are used on virtually every single construction site.

There are many hazards created by the use of this equipment for those who operate it and especially for those who work around the equipment. It is easy to become complacent when working around these machines every single workday.

The Center for Construction Research and Training states that heavy and mobile equipment were responsible for 7,681 construction worker deaths in the last two decades

It is important to continually remind yourself of the hazards of working around heavy equipment.

Hazards Created by Heavy Equipment:

There are many different hazards associated with heavy equipment. It is impossible to list every single hazard and scenario during one safety talk.

The two major hazards associated with these work tasks that are responsible for the majority of injuries and fatalities.

1. Struck-by Incidents- One of the biggest exposures for a fatality on a construction site is ground personnel being struck by moving equipment.

OSHA states approximately 75% of struck-by fatalities involve heavy equipment such as trucks or cranes. It is everyone’s responsibility to look out for one another while working around this equipment.

Work areas where heavy equipment is operated should be clearly marked and barricaded. Unnecessary foot traffic should be eliminated in these barricaded work areas.

Ground personnel entering a work area where there is equipment operating need to make their presence known to all operators in the area.

Operators should avoid backing whenever possible and need to stop their work task if they lose sight of any ground personnel.

A spotter should be used if equipment is operating in a tight area or when operating around ground personnel.

In certain situations, it could be more hazardous to use a spotter. Plan work tasks accordingly and eliminate the need for a spotter if possible.

2. Caught-in or Between Incidents - These incidents are similar to struck-by incidents, however there are differences.

A struck-by incident is when an object striking a person causes the injury. A caught-in or between incident is when there is an injury due to crushing between two objects.

An excavator bucket swinging around and striking a person in an open field would be a struck-by incident.

An excavator counterweight that turns and pins a person against a wall would be a caught-in or between incidents.

Many of the same safeguards discussed above will protect workers from being involved in a caught-in or between incidents.

One important safeguard in protecting yourself from these incidents is to stay out of the line of fire and always leave yourself an "out."

You should first always consider the safest place to be around equipment with regards to the line of fire.

Never put yourself in a situation where you do not have an out to escape danger.

It is important to always be able to get out of the way if other safeguards fail and you are put in a situation where you can become a victim of these incidents.